



## SUPREME-X OUTDOOR LED DISPLAY

Supreme-X uses the highest-quality components to deliver the brightest image quality and flicker-free video to catch the eye of the viewer. Suitable for 24/7 operations in the harshest of environments, these rugged displays offer high-end performance at attractive prices. The cabinets are seamlessly connected together to maximize the viewer's viewing experience without any visual hardware interface.

### FEATURES

- **Lightweight Design**
- **Rugged and Durable**
- **Creative Installations**
- **No Ongoing Costs**



\*The picture shown is for illustration purpose only. Actual product may vary due to product enhancement.

## TECHNICAL PARAMETERS FOR SUPREME-X

| Parameters                                  | Values                 |
|---|------------------------|
| Pixel Configuration                         | SMD 3 in 1             |
| Pitch(mm)                                   | 3.91                   |
| Cabinet Resolution(WxH)                     | 128 x 256              |
| Cabinet Size(WxH)                           | 500 mm x 1000 mm       |
| Cabinet Material                            | Die – Cast Aluminium   |
| Pixel Density(pixel/ m <sup>2</sup> )       | 65536                  |
| Dimming Capability                          | 256 Levels             |
| Brightness(nits)                            | 6000                   |
| Horizontal Viewing Angle(° )                | 160                    |
| Vertical Viewing Angle(° )                  | 140                    |
| Colour Processing                           | 16 bit                 |
| Contrast Ratio                              | 5000:1                 |
| Max. Power Consumption (W/ m <sup>2</sup> ) | 800                    |
| Ingress Protection (Front & Rear)           | IP66                   |
| Power Supply                                | AC100~240V (50/60Hz)   |
| Frame Rate(Hz)                              | 50&60                  |
| Refresh Rate(Hz)                            | 3840                   |
| Lifetime(hrs)                               | 100,000                |
| Operation Temperature(°C )                  | -10~50                 |
| Storage Temperature(°C )                    | -20~60                 |
| Operation Humidity(RH)                      | 10~90% no condensation |
| Storage Humidity(RH)                        | 10~95% no condensation |

*Design and specifications are subject to change without notice.*